



DEOTEC PREMIUM PLUS SEMI SYNTHETIC

PRODUCT DESCRIPTION:

DEOTEC PREMIUM PLUS is a premium performance semi synthetic low emission heavy-duty engine oil designed for naturally aspirated and turbo-charged 4stroke diesel and petrol engines in on- and off-highway and construction machinery applications. It is formulated with a range of latest technology dispersant, detergent, oxidation inhibition, anti-wear, anti-corrosion, viscosity improver and foam suppression additives, and is recommended for extended drain intervals.

APPLICATION:

It is recommended for 4stroke naturally aspirated and turbo-charged diesel engines, meeting Euro IV, Euro V, and the newest Euro VI emission requirements where permitted by the OEM and is suitable for use in engines with global after-treatment systems such as Exhaust Gas Recirculation (EGR), Diesel Particulate Filter (DPF), and Selective Catalytic Reduction (SCR).

FEATURES & BENEFITS:

- Helps keep piston rings, piston lands and valves clean, and offers effective soot dispersancy and wear control, optimising engine service life and maintenance costs.
- Latest technology dispersant, detergent, oxidation inhibition, anti-wear, anti-corrosion, viscosity improver, and foam suppression protection.
- Formulated to reduce emission control system cleaning and maintenance, improving Diesel Particulate Filter (DPF) life
- Advanced semi-synthetic base oil and additive technology helps control oxidation, sludge and oil thickening, offering extended oil drain intervals.

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

- API CJ-4/SN
- ACEA E9/E11
- DTFR 15B1101
- Caterpillar ECF-3
- MAN M3477
- VOLVO VDS-4
- Renault RLD3
- DDC 93K218
- Mack EO-O PP
- Cummins CES 20081
- DEUTZ DQC III-18 LA
- FORD WSS-M2C171-F1

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	DEOTEC PREMIUM PLUS	
			10W30	10W40
Grade			10W30	10W40
Kinematic Viscosity @ 104°F /40°C	D7042	cSt	TBR	TBR
Kinematic Viscosity @ 212°F /100°C	D7042	cSt	11.7	15.1
Viscosity Index (min)	D2270	-	145	145
Density@15°C/ 60°F	D4052	g/cm ³	TBR	TBR
Flash Point (min)	D92	°C	220	220
Pour Point (max)	D97	°C	-36	-36
TBN	D2896	mg KOH/g	10	10
CCS	D5293	m.Pa.S	<7000 (-25°C)	<7000 (-25°C)

DISCLAIMER: The test data provided above is for reference purposes and is not a strict specification, as variations within acceptable production tolerances may occur. Phoenix reserves the right to update or revise this test data. For the most accurate and up-to-date information, please consult the latest version of this Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website Phoenixlubricants.com