



GLIDE A PLUS MINERAL

PRODUCT DESCRIPTION:

GLIDE A PLUS is a versatile transmission fluid specifically designed for use in automatic gearboxes requiring GM Type A Suffix A specifications. Its specialized formulation ensures exceptionally smooth operation of torque converters and fluid couplings in automatic transmissions, delivering reliable performance and efficiency.

APPLICATION:

GLIDE A PLUS is suitable for use in automatic transmissions of passenger cars and light-duty trucks as well as in other power shift transmissions, industrial torque converters, power steering systems and manual transmissions, where a low-viscosity fluid of GM ATF TYPE A quality is specified.

FEATURES & BENEFITS:

- Excellent oxidation stability
- High viscosity index
- Corrosion prevention
- Smoothens transmission process
- Foaming resistance
- Controlled friction properties

PERFORMANCE LEVELS: Meets or Exceeds:

- GM Type A Suffix A

TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	GLIDE A PLUS
Grade			Type A
Kinematic Viscosity @ 104°F /40°C	ASTM D7042	cSt	52
Kinematic Viscosity @ 212°F /100°C	ASTM D7042	cSt	7.5
Viscosity Index	ASTM D2270	-	106
Density@15°C/ 60°F	ASTM D4052	g/cm ³	TBR
Flash Point (min)	ASTM D92	°C	220
Pour Point (max)	ASTM D97	°C	-27

DISCLAIMER: The test data provided above is for reference purposes and is not a strict specification, as variations within acceptable production tolerances may occur. Phoenix reserves the right to update or revise this test data. For the most accurate and up-to-date information, please consult the latest version of this Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website Phoenixlubricants.com