



GLIDE ATF+4

SYNTHETIC

PRODUCT DESCRIPTION:

GLIDE ATF+4 automatic transmission fluid is specially formulated for use in a wide range of Japanese, Korean, and Chrysler vehicles requiring ATF+4 or earlier specifications. It delivers exceptional performance at low temperatures and enhanced anti-shudder characteristics. GLIDE ATF+4 is suitable for use in transmissions, hydraulic systems, and power steering units from American, European, Korean, Japanese, and other global manufacturers that specify Chrysler ATF+4, ATF+3, or ATF+2 fluids.

FEATURES & BENEFITS:

- Excellent flow properties at low start-up temperatures and high operating temperatures
- Improved shift performance and vehicle drivability/improved shudder performance
- Good viscosity stability
- Excellent oxidation stability, less fluid breakdown in high-temperature service
- Dependable protection against rust and corrosion
- Provides more assured wear protection for maximum transmission/transaxle life
- Engineered with superior base oils to ensure superb low and high temperature performance

APPLICATION:

- Automatic transmissions specially formulated for Chrysler vehicles, including Dodge, Plymouth, Eagle and certain Jeeps, that require a fluid meeting ATF+4 specification.
- Mitsubishi and Hyundai applications where an MS-9602 type fluid is specified.
- Services that specify an ATF+, ATF+2 and ATF+3 type fluid, including certain manual transmissions, transfer cases and power steering units (1999 and later).

PERFORMANCE LEVELS: Meets or Exceeds:

- Chrysler ATF+4® Requirements
- Chrysler MS-9602

TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	GLIDE ATF+4
Kinematic Viscosity @ 104°F /40°C	ASTM D7042	cSt	TBR
Kinematic Viscosity @ 212°F /100°C	ASTM D7042	cSt	7.30
Viscosity Index (min)	ASTM D2270	-	140
Density@15°C/ 60°F	ASTM D4052	g/cm ³	TBR
Flash Point (min)	ASTM D92	°C	200
Pour Point (max)	ASTM D97	°C	-42
Viscosity Brookfield @ -40 °C	ASTM D2983	mPa.s (cP)	8400

DISCLAIMER: The test data provided above is for reference purposes and is not a strict specification, as variations within acceptable production tolerances may occur. Phoenix reserves the right to update or revise this test data. For the most accurate and up-to-date information, please consult the latest version of this Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website Phoenixlubricants.com