



GLIDE II PLUS

MINERAL

PRODUCT DESCRIPTION:

GLIDE II PLUS is a high-quality automatic transmission oil formulated with highly refined base stocks and advanced additive technology. Designed for use in passenger cars and light commercial vehicles, it helps reduce transmission chatter, ensuring smooth and quiet operation at all speeds and under all working conditions. GLIDE II PLUS delivers excellent oxidation and thermal stability, friction control, cleanliness, load-carrying capacity, and protection against wear and corrosion, maximizing the lifespan of your transmission.

APPLICATION:

Suitable for automatic gearboxes of passenger cars, power steering, vans, truck and buses where the manufacturer recommends an ATF GM Dexron II D.

FEATURES & BENEFITS:

- Very high viscosity index linked with an excellent viscosity stability in operation
- Very low pour point
- Very good thermal stability
- Excellent resistance to oxidation
- Friction properties specific to the requirements.

PERFORMANCE LEVELS: Meets or Exceeds:

- GM DEXRON IID
- CHRYSLER +3
- VOITH H55.6335
- VOLVO 97355
- FORD ESP-M2C138-CJ / ESP-M2C166-H
- ALLISON TES 389, ALLISON TES 228(C4)
- MB 236.1/236.5/236.7
- ZF TE-ML-04D / 09 / 11A / 14A
- BMW 81 22 9 400 272/81 22 9 400 275/81 22 9 407 738
- CAT TO-2
- TOYOTA TII/2
- MAN 339 TYPE L2/V1
- OPEL 19 40 700 / 19 40 707
- MITSUBISHI SP / SP2/ BTR

TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	GLIDE II PLUS
Kinematic Viscosity @ 104°F /40°C	ASTM D7042	cSt	TBR
Kinematic Viscosity @ 212°F /100°C, min	ASTM D7042	cSvt	7.1
Viscosity Index	ASTM D2270	-	140
Density@15°C/ 60°F	ASTM D4052	g/cm ³	TBR
Flash Point (min)	ASTM D92	°C	200
Pour Point (max)	ASTM D97	°C	-42

DISCLAIMER: The test data provided above is for reference purposes and is not a strict specification, as variations within acceptable production tolerances may occur. Phoenix reserves the right to update or revise this test data. For the most accurate and up-to-date information, please consult the latest version of this Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website Phoenixlubricants.com