



GLIDE UTTO SEMI SYNTHETIC

PRODUCT DESCRIPTION:

GLIDE UTTO is a premium, high-performance multipurpose tractor lubricant designed to meet or exceed the demands of transmission and hydraulic systems. It is especially effective at minimizing wet brake and Power Take-Off (PTO) chatter. With superior wear and corrosion protection and exceptional anti-friction properties, GLIDE UTTO enhances the performance and reliability of agricultural and commercial tractors operating across diverse environments and conditions.

APPLICATION:

GLIDE oil is specifically designed for agricultural machinery, offering optimal performance for gearboxes, engines, hydraulic systems, and immersion brakes in heavy-duty tractors.

FEATURES & BENEFITS:

- Guarantees easy gear changing
- High pressure-absorption capability
- Stable to oxidation
- High resistance to aging
- Universal application
- Rationalizes storage
- High wear resistance
- Good coldstart behavior

PERFORMANCE LEVELS: Meets or Exceeds:

- API GL-4
- ALLISON C4
- Case MS 1204,6,7,9
- Caterpillar TO-2
- Ford / NewHolland FNHA-2-C-201.00
- Ford M2C-48B/C • Ford M2C-159A
- Ford M2C-86B/C • Ford M2C-134 A/B/C/D
- New Holland NH 410B
- John Deere J20 A/B/C, J14 B/C
- Massey Ferguson M1135, M1141, M1143, M 1145
- ZF TE-ML-03E, 05F, 06K

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	GLIDE UTTO	
Grade			10W-20	10W-30
Kinematic Viscosity @ 104°F /40°C	D7042	cSt	TBR	TBR
Kinematic Viscosity @ 212°F /100°C	D7042	cSt	9.0	11.6
Viscosity Index	D2270	-	140	140
Density@15°C/ 60°F	D4052	g/cm ³	TBR	TBR
Flash Point (min)	D92	°C	220	220
Pour Point (max)	D97	°C	-39	-39

DISCLAIMER: The test data provided above is for reference purposes and is not a strict specification, as variations within acceptable production tolerances may occur. Phoenix reserves the right to update or revise this test data. For the most accurate and up-to-date information, please consult the latest version of this Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website Phoenixlubricants.com