



WHEELER 4T PRO

SYNTHETIC / SEMI SYNTHETIC / MINERAL

PRODUCT DESCRIPTION:

WHEELER 4T PRO is specially recommended for high-performance 4-stroke motorcycles, delivering exceptional power efficiency and acceleration. It exceeds fuel economy and engine cleanliness standards while providing excellent protection for the engine. Designed to ensure superior clutch operation under all driving conditions, WHEELER 4T PRO maintains high engine power and supports longer oil drain intervals, making it a reliable choice for optimal performance.

APPLICATION:

Recommended for all motorcycles with 4T engines. Suitable for Honda, Yamaha, Suzuki, Kawasaki, Korean and Chinese motorcycles.

FEATURES & BENEFITS:

- Excellent shear stability
- Provides high temperature protection
- Outstanding wet clutch protection for maximum power transfer and smooth shifting
- Excellent wear and corrosion protection
- Maximizes power and acceleration
- Added protection against harmful deposits

PERFORMANCE LEVELS: Meets or Exceeds:

- API SJ
- JASO MA

TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	WHEELER 4T PRO						
			5W-40	10W-30	10W-40	10W-60	20W-40	20W-50	20W-60
Grade			5W-40	10W-30	10W-40	10W-60	20W-40	20W-50	20W-60
Kinematic Viscosity @ 104°F /40°C	ASTM D7042	cSt	TBR	TBR	TBR	TBR	TBR	TBR	TBR
Kinematic Viscosity @ 212°F /100°C	ASTM D7042	cSt	14.8	11.9	14.7	24.9	14.9	19.8	23.5
Viscosity Index (min)	ASTM D2270	-	160	145	145	145	120	120	120
Density@15°C/ 60°F	ASTM D4052	g/cm ³	TBR	TBR	TBR	TBR	TBR	TBR	TBR
Flash Point (min)	ASTM D92	°C	220	220	220	220	220	220	220
Pour Point (max)	ASTM D97	°C	-39	-36	-36	-36	-24	-24	-24
TBN	ASTM D2896	mg KOH/g	6	6	6	6	6	6	6
CCS, °C	ASTM D5293	m.Pa.S	<6600 (-30°C)	<7000 (-25°C)	<7000 (-25°C)	<7000 (-25°C)	<9500 (-15°C)	<9500 (-15°C)	<9500 (-1°C)

DISCLAIMER: The test data provided above is for reference purposes and is not a strict specification, as variations within acceptable production tolerances may occur. Phoenix reserves the right to update or revise this test data. For the most accurate and up-to-date information, please consult the latest version of this Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website Phoenixlubricants.com