



DEOTEC X-TRA

FULLY SYNTHETIC

PRODUCT DESCRIPTION:

DEOTEC X-TRA is fully synthetic diesel engine oil designed for the most severe performance requirements of highly powered turbocharged engines of leading automobile companies. This oil is fuel saving and reduces maintenance expenses for machines and engines. Resists oil thickening and the formation of carbon, varnish and sludge deposits. Helps prolong engine life.

APPLICATION:

Recommended for modern heavy duty engines, wide range of turbo-charged or naturally aspirated diesel engines as well as all kinds of gasoline engines, generators, trucks, construction cars, passenger cars or mixed car group comprising diesel and gasoline cars. The oil is suitable for high speed, four stroke cycle diesel engines used on heavy duty applications. This oil is also an excellent choice for mixed fleet services.

FEATURES & BENEFITS:

- Fuel saving and reduces maintenance expenses for machines and engines.
- Very long oil changing period.
- Resists oil thickening and the formation of carbon, varnish and sludge deposits.
- Good viscosity control.
- Prolonged engine life.
- Safeguards the moving parts.
- Properly balanced detergency and dispersancy ensures a clean engine.

PERFORMANCE LEVELS: Meets and Exceeds

- API CG-4/SJ
- MB 228.3
- ACEA A3/B4
- MAN 3275
- VOLVO VDS
- MTU Type-2
- MACK EO-L
- Allison C4

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	DEOTEC X-TRA			
			0W-30	0W-40	5W-30	5W-40
Grade			0W-30	0W-40	5W-30	5W-40
Kinematic Viscosity @ 104°F /40°C	D7042	cSt	TBR	TBR	TBR	TBR
Kinematic Viscosity @ 212°F /100°C	D7042	cSt	12.1	15.3	11.9	15
Viscosity Index (min)	D2270	-	160	170	160	160
Density@15°C/ 60°F	D4052	g/cm ³	TBR	TBR	TBR	TBR
Flash Point (min)	D92	°C	220	220	220	220
Pour Point (max)	D97	°C	-39	-39	-39	-39
TBN	D2896	mg KOH/g	9.5	9.5	9.5	9.5
CCS	D5293	m.Pa.S	<6200 (-35°C)	<6200 (-35°C)	<6600 (-30°C)	<6600 (-30°C)

DISCLAIMER: The test data provided above is for reference purposes and is not a strict specification, as variations within acceptable production tolerances may occur. Phoenix reserves the right to update or revise this test data. For the most accurate and up-to-date information, please consult the latest version of this Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website Phoenixlubricants.com

