



IGNITE ACTIV MINERAL

PRODUCT DESCRIPTION:

IGNITE ACTIV is a blend of mineral oils with high performance additives recommended for use in a wide range of applications including gasoline and light duty diesel engines found in passenger cars, agricultural and construction machineries and certain hydraulic systems. They are blended to meet API service classification SC/CC requirements.

APPLICATION:

Gasoline and light duty diesel engines found in passenger cars. Farm and construction equipment, stationary diesel engines and four stroke engines where OEM recommends API SC/CC.

FEATURES & BENEFITS:

- Superior viscosity retention
- Pressure drop prevention
- Low volatility
- Wear and friction protection
- Natural thermal stability

PERFORMANCE LEVELS: Meets or Exceeds:

- API Service Category SC/CC

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	IGNITE ACTIV (MINERAL)			
			20W-50	60	50	40
Grade			20W-50	60	50	40
Kinematic Viscosity@ 104°F /40°C	D-7042	cSt	TBR	TBR	TBR	TBR
Kinematic Viscosity@ 212°F /100°C	D-7042	cSt	19.5	25.6	20	14.5
Viscosity Index (min)	D-2270	-	130	145	100	95
Density@15°C/ 60°F	D-4052	g/cm ³	TBR	TBR	TBR	TBR
Flash Point (min)	D-92	°C	236	232	254	250
Pour Point (max)	D-97	°C	-24	-24	-15	-15
TBN	D-2896	Mg KOH/g	6	6	6	6
CCS, (°C)	D-5293	m.Pa.S	<6600 (-30°C)	<9500 (-15°C)	--	--

DISCLAIMER: The test data provided above is for reference purposes and is not a strict specification, as variations within acceptable production tolerances may occur. Phoenix reserves the right to update or revise this test data. For the most accurate and up-to-date information, please consult the latest version of this Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website Phoenixlubricants.com