



IGNITE XTREME FULLY SYNTHETIC

PRODUCT DESCRIPTION:

IGNITE XTREME is a top-tier fully synthetic engine oil, crafted with high-performance base stocks and advanced additive technology. It provides exceptional engine protection while preventing deposit and sludge buildup, ensuring optimal performance in both city and highway driving conditions.

APPLICATION:

Recommended for all naturally aspirated, fuel injected, turbo-charged and multi-valve passenger car engines without particulate filters.

FEATURES & BENEFITS:

- Superior viscosity retention
- Oxidation resistant
- Outstanding wear and friction protection
- Excellent detergency and dispersancy
- Easy start at low temperatures
- Excellent protection against sludge and varnish build-up

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

SAE GRADES	5W-30	5W-40
API	SJ/CF	SJ/CF
ACEA	A1/B1	A3/B3
ILSAC	GF-2	GF-2
FORD	WSS-M2C-913A/913B	-

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	IGNITE XTREME	
			5W-30	5W-40
SAE Grades			5W-30	5W-40
Kinematic Viscosity @ 104°F /40°C	D445	cSt	TBR	TBR
Kinematic Viscosity @ 212°F /100°C	D445	cSt	10.1	14.5
Viscosity Index (min)	D2270	-	160	160
Density@15°C/ 60°F	D4052	g/cm ³	TBR	TBR
Flash Point (min)	D92	°C	220	220
Pour Point (max)	D97	°C	-39	-39
TBN	D2896	mg KOH/g	6	6
CCS	D5293	m.Pa.S	<6600 (-30°C)	<6600 (-30°C)

DISCLAIMER: The test data provided above is for reference purposes and is not a strict specification, as variations within acceptable production tolerances may occur. Phoenix reserves the right to update or revise this test data. For the most accurate and up-to-date information, please consult the latest version of this Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website Phoenixlubricants.com