



IGNITE XTREME SEMI SYNTHETIC

PRODUCT DESCRIPTION:

IGNITE XTREME is a high-quality semi-synthetic multi-grade engine oil, formulated with highly refined base stocks and advanced additive technology. It offers exceptional engine protection while preventing dirt and sludge buildup, making it ideal for older engines operating in both city and highway driving conditions.

APPLICATION:

Suitable for gasoline/diesel/CNG/LNG engines.

FEATURES & BENEFITS:

- Superior viscosity retention
- Oxidation resistant
- Wear and friction protection
- Engine Cleanliness and low combustion residue
- Excellent detergency and dispersancy
- Excellent protection against sludge and varnish deposits

PERFORMANCE LEVELS: Meets or Exceeds:

- API Service Category SJ/CF

TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	IGNITE XTREME	
Grade			10W-30	10W-40
Kinematic Viscosity @ 104°F /40°C	ASTM D7042	cSt	TBR	TBR
Kinematic Viscosity @ 212°F /100°C	ASTM D7042	cSt	11.6	15
Viscosity Index (min)	ASTM D2270	-	145	145
Density@15°C/ 60°F	ASTM D4052	g/cm ³	TBR	TBR
Flash Point (min)	ASTM D92	°C	220	220
Pour Point (max)	ASTM D97	°C	-39	-39
TBN	ASTM D2896	mg KOH/g	6	6
CCS	ASTM D5293	m.Pa.S	<6600(-30°C)	<6600(-30°C)

DISCLAIMER: The test data provided above is for reference purposes and is not a strict specification, as variations within acceptable production tolerances may occur. Phoenix reserves the right to update or revise this test data. For the most accurate and up-to-date information, please consult the latest version of this Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website Phoenixlubricants.com