



GLIDE DCT DUAL CLUTCH TRANSMISSION FLUID

PRODUCT DESCRIPTION:

GLIDE DCT is a fully synthetic transmission fluid specifically formulated for passenger cars and vans equipped with Dual Clutch Transmissions. Utilizing advanced synthetic technology, it delivers essential component protection and friction control, crucial for the optimal performance and durability of dual clutch systems.

APPLICATION:

- Suitable for use in a wide range of vehicles fitted with DCT gearboxes featuring Double Clutch Transmission and Double-Wet Clutch Transmission design.
- Especially suitable for Dual Clutch Transmission (DCT) supplied by ZF, GETRAG or BORG WARNER and used by the main car manufacturers: VW-AUDI-SEAT-SKODA, BMW, PORSCHE, FORD, OPEL, PSA Peugeot-Citroën, RENAULT and NISSAN.
- Also suitable for some mechanical gearboxes requiring gear oil with very low viscosity grade such as SAE 75W.

FEATURES & BENEFITS:

- Optimum stability to aging
- Excellent wear resistance
- Outstanding resistance to oxidation
- Very good low-temperature properties
- Excellent shear stability
- Excellent viscosity/temperature properties

TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	GLIDE DCT
Kinematic Viscosity @ 104°F /40°C	ASTM D7042	cSt	TBR
Kinematic Viscosity @ 212°F /100°C	ASTM D7042	cSt	7.2
Viscosity Index	ASTM D2270	-	140
Density at 15 °C	ASTM D4052	kg/m ³	TBR
Flash Point COC	ASTM D92	°C	200
Pour Point (max)	ASTM D97	°C	-42

PERFORMANCE LEVELS: Meets or Exceeds:

AUDI	G 009 317, G 052 171, G 052 178, G 052 182, G 052 512, G 052 527, G 052 529, G 052 726, G 052 798, G 055 512, G 055 529, G 070 726, S-tronic, TL 52 182
BMW	83 22 0 306 816, 83 22 0 397 244, 83 22 0 440 214, 83 22 2 147 477, 83 22 2 148 578, 83 22 2 148 579, 83 22 2 167 666, 83 22 2 409 710, DCTF-1, DKG, DTF 1, MTF- LT-3, MTF-LT-5
CITROËN	1618078480, 9730 A8, 9734 S2, DCS, JWS 2271
DS (CAPSA)	1618078480, 9730 A8, 9734 S2, DCS, JWS 2271
FIAT	9.55550-DA11, 9.55550-MZ2, 9.55550-MZ6, Tutela Transmission Gearforce
FORD	1 490 761, 1 490 763, POWERSHIFT, WSS-M2C200-D2, WSS-M2C200-D3, WSS-M2C200-E1, WSS-M2C936-A
HONDA	MTF-III
JAGUAR LAND ROVER	PENTOSIN FFL-3
LEXUS	#1f, #0888, 0888581001, JWS 2271, LF, LV 75W MT
MERCEDES-BENZ	MB 236.24, SLS A 001 989 86 03
MITSUBISHI	Diamond Queen SSTF-1



NISSAN	DCT Fluid, GR6, LV MT-1
PEUGEOT	1618078480, 9730 A8, 9734 S2, JWS 2271
PORSCHE	PENTOSIN FFL-3, 000 043 20, 000 043 305 63, 043 207 29, 043 207 30, 999 917 080 00, 999 917 546 00, PDK, TF 0870
RENAULT	BOT 450, DC4, EDC
SEAT	G 009 317, G 052 171, G 052 178, G 052 182, G 052 512, G 052 527, G 052 529, G 052 726, G 052 798, G 055 512, G 055 529, G 070 726, TL 52 182
SKODA	G 009 317, G 052 171, G 052 178, G 052 182, G 052 512, G 052 527, G 052 529, G 052 726, G 052 798, G 055 512, G 055 529, G 070 726, TL 52 182
SUZUKI	99000-22B27-036
TOYOTA	0888581001, JWS 2271, LF, LV 75W MT
VOLVO	1161520-7, 1161838, BOT 341
VW	DSG, G 009 317, G 052 171, G 052 178, G 052 182, G 052 512, G 052 527, G 052 529, G 052 726, G 052 798, G 055 512, G 055 529, G 070 726, TL 52 182

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website Phoenixlubricants.com