



BOREAS TYPE D READY TO USE COOLANT

PRODUCT DESCRIPTION:

BOREAS Type D is a next-generation, ready-to-use ethylene glycol-based antifreeze/coolant. It is completely free of silicates, nitrites, amines, phosphates, and boron, ensuring advanced protection for your vehicle's cooling system without the use of potentially harmful additives.

APPLICATION:

It is recommended for use in the internal combustion engines of cars, trucks, construction machinery, agricultural tractors and stationary engines.

FEATURES & BENEFITS:

- Outstanding corrosion protection
- Contains no amines, nitrites or phosphates
- Excellent antifoaming properties.
- Anti-cavitation, preventing retention of air, ensuring the good performance of the pump.
- Prevents the build-up of deposits, keeping the cooling system clean.
- Long life service product

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

- Renault/ RVI Type D
- AFNOR NF R 15-601
- BS 6580/5117
- ASTM D 3306
- SAE J 1034

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	BOREAS TYPE D
pH	D1278	cSt	8.3
Freezing Point	D1177	°C	-26
Boiling Point	D1120	cSt	111
Density at 15.5C	D4052	g/cm3	TBR

DISCLAIMER: The test data provided above is for reference purposes and is not a strict specification, as variations within acceptable production tolerances may occur. Phoenix reserves the right to update or revise this test data. For the most accurate and up-to-date information, please consult the latest version of this Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website Phoenixlubricants.com