



DRIVE 2330 MANUAL GEAR OIL

PRODUCT DESCRIPTION:

DRIVE 2330 is a high-quality transmission oil designed for use in almost all manual gearboxes of passenger cars. It is particularly recommended for PSA manual gearboxes, offering an extended drain interval and a friction modifier additive tailored to the specific n eeds of PSA manual transmissions.

APPLICATION:

DRIVE 2330 is tested under strict conditions, this oil meets the general performance requirements of most brands and models in all weather conditions.

FEATURES & BENEFITS:

- Smooth gear shifting.
- · Significantly extended transmission life
- · High resistance to oil degradation
- Provides good protection against wear and corrosion
- Reduced cost of maintenance due to long drain intervals

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

SAE GRADES	75W-80		
API	GL-4		
PSA	B71 2330		
PSA	9730 A8		
MB	235.10		
FORD	WSDM2C200-D		
FORD	ESDM2C186-A		
GM	1940182		
GM	1940768		
HONDA	MTF 94		
VOLVO	97308/97309/97310		
NISSAN	MT-XZ		

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	DRIVE 2330
			75W-80
KV@ 104°F /40°C	D7042	cSt	TBR
KV @ 212°F /100°C	D7042	cSt	9.1
Viscosity Index	D2270	-	140
Density@15°C	D4052	g/cm3	TBR
Flash Point (min)	D92	°C	200
Pour Point (max)	D97	°C	-42
Brookfield Viscosity	D2983	ср	142,000(-40C)

DISCLAIMER: The test data provided above is for reference purposes and is not a strict specification, as variations within acceptable production tolerances may occur. Phoenix reserves the right to update or revise this test data. For the most accurate and up-to-date information, please consult the latest version of this Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website Phoenixlubricants.com