



DRIVE G5 GEAR OIL

PRODUCT DESCRIPTION:

DRIVE G5 is a fully synthetic axle lubricant crafted from high-quality base oils and advanced performance additives. It ensures precise friction control and excellent resistance to aging. Specially developed for rear-wheel drive gearboxes with or without limited-slip differentials, this performance-optimized rear-axle transmission oil reduces torque loss and boosts axle drive efficiency.

APPLICATION:

DRIVE G5 is specifically designed for the high demands of BMW rear-wheel drive gearboxes. The operating instructions of the vehicle and transmission manufacturers must be followed.

FEATURES & BENEFITS:

- Excellent viscosity/temperature properties
- Reduces running noise
- Outstanding corrosion protection
- Excellent wear resistance
- Very compatible with seals
- High pressure-absorption capability
- For extended oil-change intervals
- Excellent resistance to aging

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

- BMW 83-22-2-413-512, API GL-5.

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	DRIVE G5
			70W-80
KV@ 104°F /40°C	D7042	cSt	TBR
KV @ 212°F /100°C	D7042	cSt	6.1
Viscosity Index	D2270	-	140
Density@15°C	D4052	g/cm3	TBR
Flash Point (min)	D92	°C	200
Pour Point (max)	D97	°C	-42

DISCLAIMER: The test data provided above is for reference purposes and is not a strict specification, as variations within acceptable production tolerances may occur. Phoenix reserves the right to update or revise this test data. For the most accurate and up-to-date information, please consult the latest version of this Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website Phoenixlubricants.com