



DRIVE X3 AUTOMOTIVE GEAR OIL

PRODUCT DESCRIPTION:

DRIVE G3 is an oil with moderate extreme pressure properties, designed for lubricating gearboxes that require a 20W-50 engine oil. It is ideal for gearboxes under low load conditions, where an API GL-3 lubricant is specified.

APPLICATION:

DRIVE G3 is recommended for gear boxes manufactured by FIAT and IVECO. Ideal for gears, non-hypoid differentials, transmissions requiring a lubricant with anti-wear characteristics. It is also suitable for certain gear boxes which cannot tolerate high levels of EP additives.

FEATURES & BENEFITS:

- Excellent oil film adhesion to metal surface
- Outstanding antiwear characteristics
- outstanding corrosion protection
- High anti foaming characteristics
- Improved shear stability for a stable viscosity during use
- Excellent resistance to again

PERFORMANCE LEVELS: Meets or Exceeds

- API GL-3, IVECO 18-1807 CLASS MG

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	DRIVE X3
			80W-90
KV@ 104°F /40°C	D7042	cSt	TBR
KV @ 212°F/100°C	D7042	cSt	18
Viscosity Index	D2270	-	140
Density@15°C	D4052	g/cm3	TBR
Flash Point (min)	D92	°C	200
Pour Point (max)	D97	°C	-27

DISCLAIMER: The test data provided above is for reference purposes and is not a strict specification, as variations within acceptable production tolerances may occur. Phoenix reserves the right to update or revise this test data. For the most accurate and up-to-date information, please consult the latest version of this Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website Phoenixlubricants.com