



## GLIDE 6HP

### AUTOMATIC TRANSMISSION FLUID

#### PRODUCT DESCRIPTION:

GLIDE 6HP is a versatile Automatic Transmission Fluid (ATF) designed for a wide range of applications. Formulated with high-quality synthetic base oils and advanced additives, it ensures optimal performance of automatic transmissions and provides reliable operation, even under demanding conditions.

#### APPLICATION:

GLIDE 6HP fluid is developed for use in the 6HP-series transmission of ZF 6HP19, 6HP21, 6HP26, 6HP28, 6HP32, 6HP34 and also for 5 speed automatic transmission 5HP-series. It is backwardly compatible with all earlier versions of ZF 4 and 5 gear passenger cars' automatic transmission.

#### FEATURES & BENEFITS:

- Excellent lubricating ability even at very low temperatures.
- Very good oxidation stability
- Protection against wear, corrosion and foam formation
- Neutral towards sealing materials
- Optimum power transmission ability

#### PERFORMANCE LEVELS / MEETS OR EXCEEDS:

- BMW ATF M 1375.4 (8322 0142516)
- Bentley Oil PY112995PA
- FORD MERCON SP/LV
- Hyundai SP-IV
- Jaguar Fluid 8432
- Land Rover TYK 500050
- Maserati Oil 231603
- Nissan Matic S
- Toyota Type WS
- VW / Audi G 055 005 A1/A2/A6
- ZF Lifeguardfluid6 (S671 090 255)
- FORD WSS- M2C 8432
- BMW ATF2
- JAGUAR C2C 8432
- ZF S671 090 252/253

#### TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	GLIDE 6HP
KV@ 104°F /40°C	D7042	cSt	TBR
KV @ 212°F /100°C	D7042	cSt	6.1
Viscosity Index	D2270	-	140
Density@15°C	D4052	g/cm3	TBR
Flash Point (min)	D92	°C	200
Pour Point (max)	D97	°C	-42

DISCLAIMER: The test data provided above is for reference purposes and is not a strict specification, as variations within acceptable production tolerances may occur. Phoenix reserves the right to update or revise this test data. For the most accurate and up-to-date information, please consult the latest version of this Technical Data Sheet (TDS).

#### HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website Phoenixlubricants.com