



GUARD 4 LV

PRODUCT DESCRIPTION:

GUARD 4 LV is a premium Brake and Clutch Fluid that meets the latest ISO 4925 Class 6 standard. Its exceptionally low-temperature viscosity ensures smoother fluid circulation through micro-valves in anti-locking systems, enhancing the responsiveness of ABS, ESP, and ASR high-pressure systems. Compared to conventional DOT 4 fluids, GUARD 4 LV boasts a higher wet boiling point, extending the product's service life.

APPLICATION:

GUARD 4 LV brake fluid can be used in all vehicles where ISO 4925 Class 6 specification is required. It is especially recommended for use in hydraulic brake and clutch systems of vehicles fitted with ABS (Anti-lock Braking System), ESP (Electronic Stability Program) and ASR (Acceleration Slip Regulation). GUARD 4 LV is mixable with DOT 3, DOT 4 and DOT 5.1 NON-SILICONE BASE products. Do not mix with silicone (DOT 5 silicone base) or mineral base fluids (LHM).

FEATURES & BENEFITS

- Optimal ABS properties.
- Exception chemical stability.
- High lubricating power.
- Exceptional low viscosity at low temperature.
- Higher Dry and Wet boiling points.
- Miscibility with all brake fluids of the same specification.

TYPICAL PROPERTIES:

PARAMETERS	GUARD 4 LV
ISO	4925 Class 6
FMVSS 116	DOT 4
SAE	J 1704
MB	331.0
VW	501.14 (TL 766-Z)
FORD	WSS-M6C65-A2/M6C57-A2
BMW	QV 34001

DISCLAIMER: The test data provided above is for reference purposes and is not a strict specification, as variations within acceptable production tolerances may occur. Phoenix reserves the right to update or revise this test data. For the most accurate and up-to-date information, please consult the latest version of this Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website Phoenixlubricants.com