



## GUARD 4 PLUS HIGH-PERFORMANCE BRAKE FLUID

### PRODUCT DESCRIPTION:

GUARD 4 PLUS is specifically formulated for heavy-duty brake systems in vehicles requiring a DOT 4 synthetic brake fluid. It is highly recommended for use in brake systems equipped with ABS. Additionally, GUARD 4 PLUS is compatible with all synthetic brake fluids of the same grade, allowing for seamless mixing.

### APPLICATION:

GUARD 4 PLUS is designed to excel within the extreme demands made on a race vehicle or by high performance drivers and exceeds all DOT4 standards. It is compatible with and will mix well with most DOT3, DOT4 or DOT 5.1 fluids.

### FEATURES & BENEFITS:

- High dry boiling point
- High wet boiling point
- High lubricating power
- Exceptional low viscosity at low temperature
- Miscibility with all brake fluids of the same specification

### PERFORMANCE LEVELS / MEETS OR EXCEEDS:

- ISO 4925 Class 6
- FMVSS 116 DOT 4
- SAE J 1704
- MB 276.40

### TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	GUARD 4 PLUS
Kinematic Viscosity @100C	D445	cSt	2.1
Kinematic Viscosity @-40C	D445	cSt	TBR
Boiling Point (Reflux)	D1120	°C	230
Wet Boiling Point	D1120	°C	180
Density@ 15°C	D4052	g/ml	TBR

**DISCLAIMER:** The test data provided above is for reference purposes and is not a strict specification, as variations within acceptable production tolerances may occur. Phoenix reserves the right to update or revise this test data. For the most accurate and up-to-date information, please consult the latest version of this Technical Data Sheet (TDS).

### HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website Phoenixlubricants.com