



OCEANIA 2T PLUS

PRODUCT DESCRIPTION:

OCEANIA 2T Plus is a high-performance, two-stroke marine outboard engine oil crafted with a specialized ashless additive system. Pre-diluted with a high flash point solvent, it ensures easy mixing with petrol under any temperature conditions. This oil is specifically designed for engines that require NMMA TC-W3 performance lubricants and operates reliably across all service environments.

APPLICATION:

OCEANIA 2T Plus is ideal for use in two-stroke engines requiring TC-W3 or earlier lubricants. It is suitable for applications such as outboard engines, motorcycles, lawn mowers, scooters, golf carts, chainsaws, and other two-stroke-powered equipment. Follow the OEM-recommended fuel/oil mix ratio for optimal performance. In the absence of specific guidance, a general recommendation is to use a 50:1 fuel/oil mix.

FEATURES & BENEFITS:

- Maintains high-power output
- Superior piston cleanliness and minimizes deposit formation
- Reduces maintenance cost due to enhanced lubricity
- Trouble free operation
- Maximizes spark plug life

PERFORMANCE STANDARDS: Meets or Exceeds:

- NMMA TC-W3
- API TC

TYPICAL PROPERTIES:

| PARAMETERS | TEST METHOD | UNIT | OCEANIA 2T PLUS |
|-------------------------------------|-------------|-------------------|-----------------|
| Kinematic Viscosity @ 104°F / 40°C | ASTM D445 | cSt | 61 |
| Kinematic Viscosity @ 212°F / 100°C | ASTM D445 | cSt | 9.1 |
| Viscosity Index | ASTM D2270 | - | 127 |
| Density@ 60°F | ASTM D4052 | g/cm ³ | TBR |
| Flash Point (min) | ASTM D92 | °C | 126 |
| Pour Point (max) | ASTM D97 | °C | -36 |

DISCLAIMER: The test data provided above is for reference purposes and is not a strict specification, as variations within acceptable production tolerances may occur. Phoenix reserves the right to update or revise this test data. For the most accurate and up-to-date information, please consult the latest version of this Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website Phoenixlubricants.com