



OCEANIA 2T

PRODUCT DESCRIPTION:

OCEANIA 2T is a high-quality, two-stroke outboard marine engine oil that meets TC-W2 standards. This premium ashless lubricant is specifically engineered to fulfill the stringent requirements of both air-cooled and water-cooled outboard engines.

APPLICATION:

OCEANIA 2T is suitable for and meets the requirements of leading outboard engine manufacturers, including Chrysler, Evinrude, Johnson, Mercury, Mariner, U.S. Marine/Force, Sears, OMC, Suzuki, Yamaha, Nissan, and Daihatsu, or in applications where NMMA TC-WII or TC-W oils are specified. It is also versatile enough for use in motorcycles, lawn mowers, scooters, golf carts, snowmobiles, personal watercraft, chainsaws, and other two-stroke-powered equipment. Always follow the OEM-recommended fuel/oil mix ratio. If no specific ratio is provided, a general recommendation of a 50:1 fuel/oil mix can be used.

FEATURES & BENEFITS:

- Minimizes piston rings from sticking to keep the engine operating smoothly and efficiently
- Protects against piston and combustion chamber deposits, rust, and corrosion
- Protects the piston from scuffing and pre-ignition problems and assures good low temperature fluidity
- Spark-plug fouling and carbon deposits are prevented so that power can be maintained longer
- Mixes easily with fuel for premix applications

PERFORMANCE STANDARDS: Meets or Exceeds:

- NMMA TC-W2, TC-W

TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	OCEANIA 2T
Kinematic Viscosity @ 104°F / 40°C	ASTM D445	cSt	58
Kinematic Viscosity @ 212°F / 100°C	ASTM D445	cSt	8.8
Viscosity Index	ASTM D2270	-	128
Density@ 60°F	ASTM D4052	g/cm ³	TBR
Flash Point (min)	ASTM D92	°C	120
Pour Point (max)	ASTM D97	°C	-36

DISCLAIMER: The test data provided above is for reference purposes and is not a strict specification, as variations within acceptable production tolerances may occur. Phoenix reserves the right to update or revise this test data. For the most accurate and up-to-date information, please consult the latest version of this Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website Phoenixlubricants.com