



PROTEC LC 150-EP-M5-Syn

PRODUCT DESCRIPTION:

PROTEC LC 150-EP-M5-Syn is a synthetic grease containing 5% MoS₂, designed for extreme pressure and multi-purpose applications in mining and construction equipment. It provides reliable protection during sustained heavy-duty operations. This advanced synthetic grease ensures excellent mobility, even in arctic winter conditions. Formulated for all-around performance, PROTEC LC 150-EP-M5-Syn strikes a balance between mobility, load-carrying capacity, and long-lasting service life.

APPLICATIONS

PROTEC LC 150-EP-M5 Syn is an extreme pressure, multi-purpose, mining, and construction equipment grease, which offers protection from sustained heavy-duty operations.

PRODUCT ADVANTAGES

- The operating temperature range is from -40 to 130
- Outstanding high-temperature oxidation stability
- Excellent extreme pressure properties
- High dropping point
- Effective corrosion protection
- Long operational life

TYPICAL PROPERTIES:

PARAMETERS	TEST METHODS	TYPICAL VALUE	
NLGI Grade	-	0/00	1
Thickener Type	-	Lithium-calcium	Lithium-calcium
Base Oil Type	-	Synthetic	Synthetic
Appearance	Visual	Smooth & Homogenous	Smooth & Homogenous
Colour	Visual	Black	Black
Work Penetration @25°C	ASTM D217	390	310 - 340
Copper Strip Corrosion 24hrs @100°C	ASTM D4048	1b	1b
Dropping Point °C, Min	ASTM D2265	N/A	190
Four Ball Weld Load, Kgf, Min	ASTM D2596	400	400
Molybdenum Content, %Wt.	ASTM D7303	5	5
Operating Temperature Range °C	INTERNAL	-50 to 130	-40 to 130
Base Oil Viscosity @40°C (Cst)	ASTM D445	150	150

DISCLAIMER: The test data provided above is for reference purposes and is not a strict specification, as variations within acceptable production tolerances may occur. Phoenix reserves the right to update or revise this test data. For the most accurate and up-to-date information, please consult the latest version of this Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website Phoenixlubricants.com