



PROTEC ND 460

PRODUCT DESCRIPTION:

PROTEC ND 460 is formulated with Bentone clay, highly refined heavy base oil, and anti-oxidant and anti-rust additives. It is designed to be resistant to water, offering reliable performance in challenging environments.

APPLICATIONS

PROTEC ND 46 grease is suitable for use within a very wide temperature range and especially at elevated temperatures for both industrial and automotive applications. The all-round properties make it suitable for various types of bearings, including temperature peaks up to 160°C.

PRODUCT ADVANTAGES

- The operating temperature range is -20°C to 160°C
- Non-melting thickener keeps consistency at high temperature
- Good water resistance properties
- Good oxidation and thermal stability
- Suitable for heavy and shock loading capabilities
- Good corrosion and rust protection

TYPICAL PROPERTIES:

PARAMETERS	TEST METHODS	TYPICAL VALUE
NLGI Grade	-	2
Thickener Type	-	Bentone Clay
Base Oil Type	-	Mineral
Appearance	Visual	Smooth & Homogenous
Color	Visual	Brown
Work Penetration @25°C	ASTM D217	265-295
Dropping Point °C, Min	ASTM D2265	Non drop
Operating Temperature Range °C	INTERNAL	-20 to 160
Base Oil Viscosity @40°C (Cst)	ASTM D445	460

DISCLAIMER: The test data provided above is for reference purposes and is not a strict specification, as variations within acceptable production tolerances may occur. Phoenix reserves the right to update or revise this test data. For the most accurate and up-to-date information, please consult the latest version of this Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website Phoenixlubricants.com