



SHIELD HT

PRODUCT DESCRIPTION:

SHIELD HT grease is formulated with calcium 12-hydroxystearate soap and high-quality base oil. Its specialized soap structure and carefully chosen additives allow it to perform at operating temperatures up to 110°C. This grease offers excellent water resistance, outstanding lubricity, protection against wear, and high corrosion resistance, making it ideal for demanding conditions.

APPLICATION

SHIELD HT grease is multipurpose economical grease is used for wet environments, sewage plant and machinery, wet industrial machinery, agricultural and farming machinery exposed to water, water pumps and bearings, and slow-moving axle.

PRODUCT ADVANTAGES

- The operating temperature range is -20°C to 110°C
- Excellent water resistance
- High mechanical stability
- Good Lubricity
- Good shear and stress stability
- Good pumpability

TYPICAL PROPERTIES:

PARAMETERS	TEST METHODS	TYPICAL VALUE		
NLGI Grade	-	1	2	3
Thickener Type	-	Calcium	Calcium	Calcium
Appearance	Visual	Smooth & Homogenous	Smooth & Homogenous	Smooth & Homogenous
Color	Visual	Yellow to Brown	Yellow to Brown	Yellow to Brown
Work Penetration @25°C	ASTM D217	310 - 340	265 - 295	220 - 250
Copper Strip Corrosion 24hrs @100°C	ASTM D4048	1b max.	1b max.	1b max.
Dropping Point °C, Min	ASTM D2265	140	140	140
Water Washout Resistance %Wt @79°C	ASTM D1264	max 10	max 10	max 10
Operating Temperature Range °C	INTERNAL	-20 to 110		
Base Oil Viscosity @40°C (Cst)	ASTM D445	90 - 110	90 - 110	90 - 110

DISCLAIMER: The test data provided above is for reference purposes and is not a strict specification, as variations within acceptable production tolerances may occur. Phoenix reserves the right to update or revise this test data. For the most accurate and up-to-date information, please consult the latest version of this Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website Phoenixlubricants.com