



SHIELD LC-EP

PRODUCT DESCRIPTION:

SHIELD LC-EP is an extreme-pressure grease known for its high resistance to water washout, providing effective protection against wear and corrosion. It is ideal for lubricating plain and rolling bearings operating under high loads and in wet environments. This grease offers superior mechanical stability, load-carrying capacity, and corrosion protection. Fortified with Ca-12 Hydroxystearate thickener, it delivers enhanced water resistance and mechanical stability, making SHIELD LC-EP a truly versatile, multipurpose grease.

APPLICATION

SHIELD LC-EP is a widely used extreme pressure grease recommended for the lubrication of plain and rolling bearings, operated under high loads and in wet environment. It is also suitable for commercial vehicle and construction equipment applications, agricultural and off-road applications. NLGI 000, 00, 0, 1 grades are suitable for centralized lubrication system where a semi fluid grease is required.

PRODUCT ADVANTAGES

- The operating temperature range is from -20°C to 130°C
- Very good rust and corrosion protection
- High-load carrying capacity
- Excellent resistance against water
- Very good anti-wear protection
- Good shear and stress stability
- Very good adhesion properties

TYPICAL PROPERTIES:

PARAMETERS	TEST METHODS	TYPICAL VALUE					
NLGI Grade	-	000	00	0	1	2	3
Thickener Type	-	Lithium					
Appearance	Visual	Smooth & Homogenous					
Color	Visual	Light Brown					
Work Penetration @25°C	ASTM D217	445 - 475	400-430	355-385	310-340	265-295	220-250
Copper Strip Corrosion, 24hrs @100°C	ASTM D4048	1b max.	1b max.	1b max.	1b max.	1b max.	1b max.
Dropping Point °C	ASTM D2265	N/A	N/A	N/A	180	180	180
Water Washout Resistance %Wt. @79°C	ASTM D1264	N/A	N/A	N/A	Max 10		
Four Ball Weld Load, Kgf, Min	ASTM D2596	200					
Operating Temperature Range, °C	INTERNAL	-20 to 130					
Base Oil Viscosity @40°C (Cst)	ASTM D445	90 -110					

DISCLAIMER: The test data provided above is for reference purposes and is not a strict specification, as variations within acceptable production tolerances may occur. Phoenix reserves the right to update or revise this test data. For the most accurate and up-to-date information, please consult the latest version of this Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website Phoenixlubricants.com