



## WHEELER 4T ULTRA SYNTHETIC / SEMI SYNTHETIC / MINERAL

### PRODUCT DESCRIPTION:

WHEELER 4T ULTRA is a multi-grade oil designed for four-stroke engines in motorcycles, scooters, and mopeds. It is formulated with high-quality base oils and a balanced additive system from leading manufacturers. This oil provides improved detergency, enhanced anti-wear and anti-foam properties, and offers excellent resistance to oxidation and corrosion, ensuring reliable engine protection and performance across various riding conditions.

### APPLICATION:

WHEELER 4T ULTRA is intended for use in four-stroke engines of scooters, mopeds, motorcycles and ATVs, which require API SG performance level, and also for motorbikes' transmissions and clutches, which need lubrication by motor oils.

### FEATURES & BENEFITS:

- Maximum engine power.
- Unsuper passed gear protection.
- Outstanding wear protection
- Excellent shear and oxidation resistance
- Better clutch "feeling"
- Excellent low temperature fluidity

### PERFORMANCE LEVELS: Meets or Exceeds:

- API SG, JASO MA

### TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	WHEELER 4T ULTRA							
			5W-30	10W-30	10W-40	10W-50	15W-40	15W-50	20W-40	20W-50
Grade			5W-30	10W-30	10W-40	10W-50	15W-40	15W-50	20W-40	20W-50
Kinematic Viscosity @ 104°F /40°C	D7042	cSt	TBR	TBR	TBR	TBR	TBR	TBR	TBR	TBR
Kinematic Viscosity @ 212°F /100°C	D7042	cSt	11.7	11.7	15.1	19.5	15	19.5	15	20
Viscosity Index (min)	D2270	-	160	145	145	145	135	135	120	120
TBN	D8698	mgKOH/g	6	6	6	6	6	6	6	6
Density@15°C/ 60°F	D4052	g/cm3	TBR	TBR	TBR	TBR	TBR	TBR	TBR	TBR
Flash Point (min)	D92	°C	220	220	220	220	220	220	220	220
Pour Point (max)	D97	°C	-39	-36	-36	-36	-33	-33	-24	-24

DISCLAIMER: The test data provided above is for reference purposes and is not a strict specification, as variations within acceptable production tolerances may occur. Phoenix reserves the right to update or revise this test data. For the most accurate and up-to-date information, please consult the latest version of this Technical Data Sheet (TDS).

### HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website Phoenixlubricants.com

