



## WHEELER SNOWMOBILE 2T 2-STROKE ENGINE LUBRICANT FOR SNOWMOBILE

### PRODUCT DESCRIPTION:

WHEELER SNOWMOBILE 2T is a high-performance, fully synthetic oil specifically designed for 2-stroke engines in snowmobiles. Formulated with carefully selected esters, it offers superior detergency and dispersancy properties. The synthetic base fluids ensure excellent low-temperature fluidity while maintaining exceptional lubrication at high operating temperatures. WHEELER SNOWMOBILE 2T delivers reliable protection and performance across all operating conditions.

### APPLICATION:

WHEELER SNOWMOBILE 2T is intended for 2-stroke engines with injector systems or lubricated by premix. It is suitable for both racing use and normal driving where very high performance is required. Product is to be used as per OEM recommended fuel/oil mix ratio. If the specific ratio is not provided, the general recommendation is to use 50:1 fuel/oil mix.

### FEATURES & BENEFITS:

- Low ash formulation prevents deposits on pistons and ports.
- Mixes instantaneously with gasoline and remains stable.
- Excellent cold flow and lubricating properties at extreme temperatures.
- Reduces friction and wear to increase engine life

### PERFORMANCE LEVELS: Meets or Exceeds:

- API TC
- ISO L-EGD
- JASO FD

### TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	WHEELER SNOWMOBILE 2T
Kinematic Viscosity @ 212°F/100°C	ASTM D7042	cSt	7.5
Kinematic Viscosity @ 104°F/40°C	ASTM D7042	cSt	41.4
Viscosity Index	ASTM D2270	-	150
TBN	ASTM D2896	Mg KOH/g	2
FLASH POINT	ASTM D92	°C	152
POUR POINT	ASTM D97	°C	-45
SPECIFIC GRAVITY	ASTM D4052	g/cm <sup>3</sup>	TBR

**DISCLAIMER:** The test data provided above is for reference purposes and is not a strict specification, as variations within acceptable production tolerances may occur. Phoenix reserves the right to update or revise this test data. For the most accurate and up-to-date information, please consult the latest version of this Technical Data Sheet (TDS).

### HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website [Phoenixlubricants.com](http://Phoenixlubricants.com)